



RG-11/60-11/60M

DROP CABLE

75 OHM COAXIAL CABLE

DESCRIPTION

RG-11/60-11/60M – Dual RG-11/60 with 11/60, No 14 AWG solid copper conductor, Fine's proprietary gas injected PE foam dielectric, bonded aluminum shielding tape, 60% coverage aluminum braid wire, 2.77 mm galvanized steel messenger, overall black PVC jacket.

CONSTRUCTION DETAILS

Inner Conductor, mm (inch)	1.63	(0.064)
Dielectric Diameter, mm (inch)	7.11	(0.280)
Outer Conductor Diameter, mm (inch)	7.32	(0.288)
Overall Cable Diameter, mm (inch)	10.2	(0.400)
Steel Messenger Diameter, mm (inch)	2.77	(0.109)
Cable Width – Web direction, mm (inch)	26.3	(1.03)

ELECTRICAL SPECIFICATIONS

Network Analyzer Swept Frequency Range	1 – 1000 MHz	
Capacitance, pF/m	53 ± 2	
Impedance, ohms	75 ± 3	
Velocity of Propagation, %	85 nominal	
Structural Return Loss, dB	-20 minimum	
Maximum Attenuation @ 20°C at Various Frequencies:	dB/100m	(dB/100 feet)
5 MHz	1.14	0.34
55 MHz	3.10	0.91
250 MHz	6.43	1.96
300 MHz	7.02	2.14
350 MHz	7.68	2.34
400 MHz	8.23	2.51
450 MHz	8.76	2.67
500 MHz	9.28	2.83
550 MHz	9.84	3.00
600 MHz	10.33	3.15
750 MHz	11.71	3.57
870 MHz	12.79	3.90
1000 MHz	13.91	4.24

REEL PACKAGING DIMENSIONS

Standard Reel Length:	500' or 1000'		
Shipping Weight:	311 kg/km	209 lbs/1000 feet	
Reel Dimensions:	Flange: 580	Drum: 240 mm	Traverse: 300 mm